

Milliken® Hyperform® HPN® 909ei

High-Performance Additive for Polypropylene


Designed for use by thermoformers in polypropylene homopolymers, Hyperform HPN 909ei is an additive that offers excellent aesthetics and has been developed using a cleaner chemistry.

In addition to providing an excellent balance of physical properties (high stiffness while maintaining good impact strength), isotropic shrinkage, and a higher heat deflection temperature (HDT), this additive yields products with excellent optical properties, including lower haze, reduced yellowing, and an overall cleaner look. This enhances the ability of end users to substitute highly recyclable polypropylene for other materials in some of their applications.

With its growing range of Hyperform HPN additives, Milliken continues to help converters to improve their processing and enhance the performance of their final PP parts.

Excellent Aesthetics

Hyperform HPN 909ei reduces the haze and the yellowness index, yielding final parts that are cleaner, clearer and more transparent, which can further enhance sustainability by allowing for more inter-material replacement.



Applications

- Food Packaging
- Drink Cups / Lids
- Trays

Cleaner Chemistry

Another factor, which is vitally important in the European Union, is that this new formulation is tailored specifically to address concerns related to migration, especially in food-contact applications. Hyperform HPN 909ei not only is derived from cleaner chemistry, but it also has one SML (Specific Migration Limit) less than Milliken's previous generation product for thermoforming, Hyperform HPN 600ei.





Hyperform® HPN® 909ei

High-Performance Additive for PP




Balanced Physical Properties

Traditional nucleating agents require customers to sacrifice impact to gain greater stiffness. Hyperform HPN 909ei delivers improved stiffness (Flexural Modulus) while maintaining the impact performance.




Isotropic Shrinkage

The unique isotropic shrinkage behavior of Hyperform HPN 909ei allows dimensionally stable, non-warping PP parts.



Heat Resistance and Crystallization Behavior

HPN 909ei provides a higher heat deflection temperature (HDT) and an increase in crystallization temperature.



Please contact your Milliken representative for any additional information.

PLEASE NOTE: As each customer's use of our product may be different, information we provide, including without limitation, recommendations, test results, samples, care/labeling/processing instructions or marketing advice, is provided in good faith but without warranty and without accepting any responsibility/liability. Each customer must test and be responsible for its own specific use, further processing, labeling, marketing, etc. All sales are exclusively subject to our standard terms of sale posted at www.milliken.com/terms (all additional/different terms are rejected) unless explicitly agreed otherwise in a signed writing.

NORTH AMERICA
Spartanburg, SC, USA
Tel: 800-910-5592
Fax: 864-503-2430
millichem@milliken.com

EUROPE
Gent, Belgium
Tel: 32-9-265-1100
Fax: 32-9-265-1195
eurochem@milliken.com

LATIN AMERICA
Sao Paulo, Brazil
Tel: 55-11-3043-7942
Fax: 55-11-3043-7096
lachim@milliken.com

LATIN AMERICA
Mexico City, Mexico
Tel: 52-55-3088 3600
Fax: 52-55-9000 2643
lachim@milliken.com

ASIA
Singapore
Tel: 65-6377-0770
Fax: 65-6377-0990
asiachem@milliken.com

ASIA
Shanghai
Tel: 86-21 6145-5555
Fax: 86-21 6145-5558
asiachem@milliken.com

ASIA
Pune, India
Tel: 91.20.6730.7501
Fax: 91.20.6730.7514
asiachem@milliken.com